

Painting station TSV

Version with Turbine TMR90E

USE



Attention! Painting station TSV IS NOT suitable for spraying on ceilings



The painting station TSV (with spray gun ASV) is suitable for lightweight and low viscosity materials (varnish).

For more information on sectors of use, see the section fields of application.

| Workable covering materials | | | | | | | | | |
|---|-----|-----|---|-----|-----|-----|-----|---|-----|
| Nozzlei Ø mm | 0,5 | 0,7 | 1 | 1,3 | 1,7 | 2,1 | 2,5 | 3 | 3,5 |
| Solvent-based and water based paints | | | | | | | | | |
| Rust preventers | | | | ✓ | ✓ | | | | |
| Fillers | | | ✓ | ✓ | | | | | |
| Flatting | | | | ✓ | ✓ | | | | |
| Micacecus (Metalised enamels) | | | | ✓ | ✓ | | | | |
| Enamels | | ✓ | ✓ | ✓ | | | | | |
| Polyurethan enamels | | | | ✓ | ✓ | | | | |

Please Note: to obtain products with good mechanical resistance and weatherability properties, observe the rules supplied by the manufacturer of covering products. Prepare the product following the instructions of the latter.

| Workable covering materials | |
|---|---|
| Water based and solvent based varnishes (enamels, rust preventers, fillers flatting, etc.) | ✓ |
| Wall paints (distempers, waterpaints, multicolor, fine quartz paints, etc.) (*) | ✓ |

(*) with kit for water- based varnish and paints item TPK04.

Fields of application

Navigation



Body and garage works

Joinery

Building

Carpentry



For more information on sectors of use see the section fields of application.

